



FINGER LIFT : FL7917, FL7915

Solvent free. Printing technology up to 2 colors. UV-resistant.
Excellent ageing. High clarity.

PRODUCT INFORMATION

Product description



Self-adhesive tape consists of Polypropylene carrier coated with high grade pressure sensitive Acrylic water based adhesive, includes non-adhesive zone for an easy peeling and reclosing a package.

Application



Excellent performance tape for an easy-to-use resealable closure of a package.

Storage conditions



One year from date received when stored at 15-30°C (59-86°F). 50% relative humidity.
Out of direct sunlight.

Surface Preparation before application



The surface to which the tape is applied should be clean, dry, and free of grease and oil.

Warranty



We recommend each user determine the suitability of the products for the intended use.

Typical values



Properties	Unit	Values FL 7917	Values FL 7915	Test Method
filmThickness total ± 5%	Mikron (mil)	35 (1.41) 55 (2.16)	50 (2.0) 70 (2.7)	PSTC-133 ASTM D-882
Tensile strength	N/mm ²	150	150	ASTM D-882
Elongation	%	210	210	PSTC-101
Adhesion to steel	N / cal	8.5 ± 2	8.5 ± 2	
Tape color		Transparent	Transparent	
Widths*	mm	30, 42	30, 42	
Lengths*	M	500, 850	500, 850	
Core width	mm (cale)	76 (3)	76 (3)	

* other sizes upon request