



Logo tape sp. z o. o.
ul. Bydgoska 18, 89-620 Pawłówko



+48 52 3355918



biuro@logotape.pl
www.logotape.pl/en

Handylift LT 11208r (PV1)

The self-adhesive carrying handle made of PET with a PCR content

PRODUCT INFORMATION

Product description



LOGO tape GREEN SERIES is the sustainable product line in our product portfolio. The LOGO tape Handylift 11208r (PV1) contains a Post-Consumer Recycled (PCR) content of 20%. The carrying zone is created by an individually printable PET film label. The parallel-wound spooling technique allows for long machine running times and short set-up times. The product design allows for trouble-free use on all common applicators.

*The calculation is based on a handle dimension of 400/200/2×100.

Application



The LOGO tape Handylift 11208r (PV1) is based on a temperature-resistant PET film with a natural rubber adhesive developed for bonding to PE films. It is universally applicable, especially for bonding to PE shrink films. The special product design, based on PET films, makes it possible to apply the carrying handle before shrinking. The LT 11208r (PV1) is suitable for heavy packages with a maximum weight of 12 kg.

Storage conditions



Store in a dry place, protected from direct sunlight.
Storage temperature: +15 to +30°C
Shelf life: 1 year from delivery date

Dimensions



Core width 180 mm	Core: 6 inches; 25 mm, 37 mm; up to 3500 m (25 mm handle width)
Core width 350 mm	Core: 6 inches; 25 mm, 37 mm; up to 7000 m (25 mm handle width)
Flat roll: 25 mm, 37 mm	Core: 3 inches; Core width = Tape width
Other dimensions are available upon request.	

Technical Data



Carrier Material	PET
Adhesive	Natural Rubber
Colors	Transparent
Total Thickness	70 µm
Adhesion to Steel	2 N/cm
Tensile Strength	min. 150 N/25 mm

In practice Logo tape products are of high quality level, which will constantly be subjected to severe control. Due to practical experience, we give all the references and recommendations to the best of one's knowledge. As the conditions of usage are consistently different, we recommend to prove the applicability of the product through your own try. In case of doubt, we will kindly advise you.